

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/25/2019

Revision date: 10/25/2019

Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Napthalene Standard  
 Product code : AL0-101352

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Phenova  
 6390 Joyce Dr. Suite 100  
 Golden, CO 80403 - United States  
 T 1-866-942-2978 - F 1-866-283-0269  
[info@phenova.com](mailto:info@phenova.com) - [www.phenova.com](http://www.phenova.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924  
 ChemTel Assistance (International) +1 813-248-0585

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapour
Acute toxicity (oral) Category 3	H301	Toxic if swallowed
Acute toxicity (dermal) Category 3	H311	Toxic in contact with skin
Carcinogenicity Category 1B	H350	May cause cancer
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour  
 H301+H311 - Toxic if swallowed or in contact with skin  
 H350 - May cause cancer  
 H370 - Causes damage to organs

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 - If swallowed: Immediately call a poison center or doctor  
 P302+P352 - If on skin: Wash with plenty of water  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P307+P311 - If exposed: Call a poison center/doctor

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center or doctor if you feel unwell  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P322 - Specific treatment (see supplemental first aid instruction on this label)  
P330 - Rinse mouth.  
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc.
methanol (Component)	(CAS-No.) 67-56-1	99.9
naphthalene (Component)	(CAS-No.) 91-20-3	0.1

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.  
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.  
First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.  
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.  
Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

No additional information available

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Napthalene Standard		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
naphthalene (91-20-3)		
ACGIH	Local name	Naphthalene
ACGIH	ACGIH TWA (ppm)	10 ppm (Naphthalene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Hematologic eff; URT & eye irr; Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
ACGIH	Regulatory reference	ACGIH 2018

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

naphthalene (91-20-3)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	10 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
methanol (67-56-1)		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

### 8.2. Appropriate engineering controls

No additional information available

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear protective gloves.

#### Eye protection:

Chemical goggles or safety glasses

#### Respiratory protection:

Wear appropriate mask

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: Colorless
	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Napthalene Standard	
ATE US (oral)	100.1 mg/kg body weight
ATE US (dermal)	300.3 mg/kg body weight
naphthalene (91-20-3)	
LD50 oral rat	> 1100 mg/kg (Rat)
LD50 dermal rat	> 2500 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
ATE US (oral)	500 mg/kg body weight
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Not classified
STOT-single exposure	: Causes damage to organs.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

## SECTION 12: Ecological information

### 12.1. Toxicity

naphthalene (91-20-3)	
EC50 Daphnia 1	2.16 mg/l (EC50; 48 h; Daphnia magna)
LC50 fish 2	0.11 mg/l (LC50; 96 h; Oncorhynchus mykiss)
Threshold limit algae 1	0.4 mg/l (EC50; 72 h; Skeletonema costatum)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

### 12.2. Persistence and degradability

Napthalene Standard	
Persistence and degradability	Not established.
naphthalene (91-20-3)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.22 g O <sub>2</sub> /g substance
ThOD	2.99 g O <sub>2</sub> /g substance
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)

### 12.3. Bioaccumulative potential

Napthalene Standard	
Bioaccumulative potential	Not established.
naphthalene (91-20-3)	
BCF fish 1	23 - 168 (BCF; 8 weeks; Cyprinus carpio)
Log Pow	3.3 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.4. Mobility in soil

naphthalene (91-20-3)	
Surface tension	0.03 N/m (100 °C)
methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value

### 12.5. Other adverse effects

Napthalene Standard	
naphthalene (91-20-3)	
methanol (67-56-1)	

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1230 Methanol (methanol ; naphthalene), 3 (6.1), II  
UN-No.(DOT) : UN1230  
Proper Shipping Name (DOT) : Methanol  
methanol ; naphthalene  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Subsidiary risk (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132  
Hazard labels (DOT) : 3 - Flammable liquid  
6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Symbols : + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group, I - Proper shipping name appropriate for international and domestic transportation  
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : 1 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

### Transportation of Dangerous Goods

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 1230 METHANOL (methanol ; naphthalene), 3 (6.1), II (12°C c.c.)

UN-No. (IMDG) : 1230

Proper Shipping Name (IMDG) : METHANOL

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Subsidiary risks (IMDG) : 6.1 - Toxic substances

Limited quantities (IMDG) : 1 L

### Air transport

Transport document description (IATA) : UN 1230 Methanol (methanol ; naphthalene), 3 (6.1), II

UN-No. (IATA) : 1230

Proper Shipping Name (IATA) : Methanol

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

Subsidiary hazards (IATA) : 6.1 - Toxic substances

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### naphthalene (91-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ : 100 lb

#### methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ : 5000 lb

### 15.2. International regulations

#### CANADA

#### naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

#### methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available



# Napthalene Standard

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### National regulations

#### naphthalene (91-20-3)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on EPA Hazardous Air Pollutant (HAPS)

#### methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

### 15.3. US State regulations

#### naphthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	5.8 µg/day	

#### methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 µg/day (inhalation); 23,000 µg/day (oral)

### SECTION 16: Other information

Revision date : 10/25/2019

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H350	May cause cancer
H370	Causes damage to organs

Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at [www.phenova.com](http://www.phenova.com) for additional terms and conditions of sale.