

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/02/2019 Revision date: 12/02/2019 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : 10K Acrolein Mix
Product code : AL0-130970

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Certified reference material for laboratory use only

1.3. Supplier

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids H225 Highly flammable liquid and vapour

Category 2

Acute toxicity (oral) H301 Toxic if swallowed

Category 3

Acute toxicity (dermal) H311 Toxic in contact with skin

Category 3

Specific target organ H370 Causes damage to organs

toxicity (single exposure)

Category 1

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapour

H301+H311 - Toxic if swallowed or in contact with skin

H370 - Causes damage to organs

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. open flames

P233 - Keep container tightly closed.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray. P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor P308+P313 - If exposed or concerned: Get medical advice/attention.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

12/02/2019 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.
methanol	(CAS-No.) 67-56-1	99
Acrolein	(CAS-No.) 107-02-8	1

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

Immediately call a poison center or doctor/physician. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Reactivity : Thermal decomposition generates : Corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

12/02/2019 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. No open flames. No smoking. Use only non-sparking tools.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated

clothing.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Comply with applicable regulations.

Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a

well-ventilated place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

10K Acrolein Mix		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

Acrolein (107-02-8)		
ACGIH	Local name	Acrolein
ACGIH	ACGIH Ceiling (ppm)	0.1 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr; pulm edema
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	0.25 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	0.1 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

methanol (67-56-1)		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)

12/02/2019 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)		
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

8.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

Eye protection:

Chemical goggles or face shield. Safety glasses

Skin and body protection:

Wear suitable protective clothing. Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):







Other information:

Odor threshold

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state : Liquid

: Colorless: characteristic

: No data available

pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour.

Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : No data available
Solubility : No data available
Log Pow : No data available

12/02/2019 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates: Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

10K Acrolein Mix		
ATE US (oral)	100.2 mg/kg body weight	
ATE US (dermal)	300.601 mg/kg body weight	
Acrolein (107-02-8)		
LD50 dermal rabbit	200 - 562 mg/kg (Rabbit, Literature study, Dermal)	
LC50 inhalation rat (mg/l)	0.018 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))	
LC50 inhalation rat (ppm)	8.3 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (gases))	
ATE US (oral)	5 mg/kg body weight	
ATE US (dermal)	200 mg/kg body weight	
ATE US (gases)	10 ppmV/4h	
ATE US (vapors)	0.018 mg/l/4h	
ATE US (dust, mist)	0.018 mg/l/4h	
methanol (67-56-1)		
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)	
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)	
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)	
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)	
ATE US (oral)	100 mg/kg body weight	
ATE US (dermal)	300 mg/kg body weight	
ATE US (gases)	700 ppmV/4h	
ATE US (vapors)	3 mg/l/4h	
ATE US (dust, mist)	0.5 mg/l/4h	
Skin corrosion/irritation	: Not classified	

12/02/2019 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

STOT-single exposure : Causes damage to organs.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion : Toxic if swallowing a small quantity of this material will result in serious health

hazard

SECTION 12: Ecological information

12.1. Toxicity

Acrolein (107-02-8)	
LC50 fish 1	19.5 μg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	0.09 mg/l (DIN 38412: German standard methods for the examination of water, waste water and sludge, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	0.061 mg/l (Other, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (I C50: 96 h; Salmo gairdneri)

12.2. Persistence and degradability

10K Acrolein Mix		
Persistence and degradability	Not established.	
Acrolein (107-02-8)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Chemical oxygen demand (COD)	1.72 g O₂/g substance	
ThOD	2 g O₂/g substance	
methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.42 g O₂/g substance	
ThOD	1.5 g O ₂ /g substance	

12.3. Bioaccumulative potential

BOD (% of ThOD)

10K Acrolein Mix	
Bioaccumulative potential	Not established.

0.8 (Literature study)

12/02/2019 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acrolein (107-02-8)		
BCF fish 1	344 (Other, 28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)	
Log Pow	-0.01 (Experimental value)	
Bioaccumulative potential	Not bioaccumulative.	
methanol (67-56-1)		
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)	
Log Pow	-0.77 (Experimental value; Other)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

Acrolein (107-02-8)		
Surface tension 0.028 N/m (20 °C)		
Log Koc	0.441 (log Koc, PCKOCWIN v1.66, Calculated value)	
Ecology - soil	Highly mobile in soil. Toxic to flora.	
methanol (67-56-1)		
Surface tension	0.023 N/m (20 °C)	
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value	

12.5. Other adverse effects

10K Acrolein Mix		
Acrolein (107-02-8)		
methanol (67-56-1)		

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1992 Flammable liquids, toxic, n.o.s. (methanol), 3 (6.1), II

UN-No.(DOT) : UN1992

Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.

methanol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Subsidiary risk (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132

Hazard labels (DOT) : 3 - Flammable liquid 6.1 - Poison





DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 243

12/02/2019 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Symbols

: G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is

transported by sea.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol), 3 (6.1), II

UN-No. (IMDG) 1992

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Class (IMDG) : 3 - Flammable liquids

: II - substances presenting medium danger Packing group (IMDG)

Subsidiary risks (IMDG) : 6.1 - Toxic substances

Air transport

Transport document description (IATA) : UN 1992 Flammable liquid, toxic, n.o.s. (methanol), 3 (6.1), II

UN-No. (IATA)

Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s. Class (IATA) : 3 - Flammable Liquids Packing group (IATA) : II - Medium Danger Subsidiary hazards (IATA) : 6.1 - Toxic substances

SECTION 15: Regulatory information

15.1. US Federal regulations

12/02/2019 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acrolein (107-02-8)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313			
Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	1 lb		
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb		
methanol (67-56-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313			
Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ 5000 lb			

15.2. International regulations

CANADA

Acrolein (107-02-8)

Listed on the Canadian DSL (Domestic Substances List)

methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Acrolein (107-02-8)

Listed on EPA Hazardous Air Pollutant (HAPS)

methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 μg/day (inhalation); 23,000 μg/day (oral)

SECTION 16: Other information

Revision date : 12/02/2019

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases:

<u> </u>		
H225	Highly flammable liquid and vapour	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H370	Causes damage to organs	

Phenova US SDS REV

12/02/2019 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

12/02/2019 EN (English US) 10/10