

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 20/11/2017 Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Custom VOA Additions Mixture

Product code : AL0-130191
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Laboratory Use Industrial/Professional use spec : Industrial

For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Phenova

6390 Joyce Dr. Suite 100

80403 Golden, CO - United States T 1-866-942-2978 - F 1-866-283-0269

info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

 Flam. Liq. 2
 H225

 Acute Tox. 3 (Oral)
 H301

 Acute Tox. 3 (Dermal)
 H311

 STOT SE 1
 H370

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

T; R23/24/25 T; R39/23/24/25

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS08

GHS02 GHS06

Signal word (CLP) : Danger

Hazardous ingredients : methanol; 2-chloroethylvinyl ether

Hazard statements (CLP) : H225 - Highly flammable liquid and vapor

H301+H311 - Toxic if swallowed or in contact with skin

H370 - Causes damage to organs

20/11/2017 EN (English US) 1/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water

P308+P313 - IF exposed or concerned: Get medical advice/attention

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use media other than water to extinguish

P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

No labeling applicable

Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]		
methanol (Component)	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X	96.5996	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370		
2-methyl-2-butanol (Component)	(CAS No) 75-85-4 (EC-No.) 200-908-9 (EC index no) 603-007-00-2	2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT SE 3, H335 Skin Irrit. 2, H315		
methylcyclohexane (Component)	(CAS No) 108-87-2 (EC-No.) 203-624-3 (EC index no) 601-018-00-7	0.2	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
cyclohexane (Component)	(CAS No) 110-82-7 (EC-No.) 203-806-2 (EC index no) 601-017-00-1	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410		
2-chloroethylvinyl ether (Component)	(CAS No) 110-75-8 (EC-No.) 203-799-6	0.2	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335		
1,2,3-trimethylbenzene (Component) substance with a Community workplace exposure limit	(CAS No) 526-73-8 (EC-No.) 208-394-8	0.0004	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335		
Name	Product identifier	Specific co	Specific concentration limits		
methanol (Component)	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X		(3 = <c 10)="" 2,="" <="" h371<br="" se="" stot="">(C >= 10) STOT SE 1, H370</c>		

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general Never give anything by mouth to an unconscious person. Call a POISON CENTER or

doctor/physician. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact Gently wash with plenty of soap and water. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with First-aid measures after eye contact water for several minutes. Obtain medical attention if pain, blinking or redness persists.

20/11/2017 EN (English US) 2/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after ingestion : If swallowed, rins

: If swallowed, rinse mouth with water (only if the person is conscious). Get immediate medical advice/attention. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact

: Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion

 $: \ \, \text{Toxic if swallowed. Swallowing a small quantity of this material will result in serious health}$

hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media

: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools.

Hygiene measures

: Wash contaminated clothing before reuse. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.

Storage conditions

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

20/11/2017 EN (English US) 3/11

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

methanol (67-56-1)		
EU	IOELV TWA (mg/m³)	260 mg/m³ (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	200 ppm (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m³)	266 mg/m³ (Alcool méthylique; Belgium; Time- weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	200 ppm (Alcool méthylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m³)	333 mg/m³ (Alcool méthylique; Belgium; Short time value)
Belgium	Short time value (ppm)	250 ppm (Alcool méthylique; Belgium; Short time value)
France	VLE (mg/m³)	1300 mg/m³ (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	1000 ppm (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m³)	260 mg/m³ (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	200 ppm (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m³)	133 mg/m³ (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m³)	266 mg/m³ Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	200 ppm Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m³)	333 mg/m³ Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	250 ppm Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
cyclohexane (110-82-7)		
EU	IOELV TWA (mg/m³)	700 mg/m³ (Cyclohexane; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	200 ppm (Cyclohexane; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m³)	350 mg/m³ (Cyclohexane; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	100 ppm (Cyclohexane; Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m³)	1300 mg/m³ (Cyclohexane; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	375 ppm (Cyclohexane; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m³)	700 mg/m³ (Cyclohexane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	200 ppm (Cyclohexane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm (Cyclohexane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

20/11/2017 EN (English US) 4/11

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexane (110-82-7)		
Netherlands	Grenswaarde TGG 8H (mg/m³)	700 mg/m³ (Cyclohexaan; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	200 ppm (Cyclohexaan; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	1400 mg/m³ (Cyclohexaan; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	400 ppm (Cyclohexaan; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m³)	350 mg/m³ Cyclohexane; United Kingdom; Time- weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	100 ppm Cyclohexane; United Kingdom; Time- weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m³)	1050 mg/m³ Cyclohexane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	300 ppm Cyclohexane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
methylcyclohexane (108-87-	2)	
Belgium	Limit value (mg/m³)	1633 mg/m³ (Méthylcyclohexane; Belgium; Time- weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	400 ppm (Méthylcyclohexane; Belgium; Time-weighted average exposure limit 8 h)
France	VME (mg/m³)	1600 mg/m³ (Méthylcyclohexane; France; Time- weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
France	VME (ppm)	400 ppm (Méthylcyclohexane; France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	400 ppm (Methyl cyclohexane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
1,2,3-trimethylbenzene (526-	73-8)	<u> </u>
EU	IOELV TWA (mg/m³)	100 mg/m³ (1,2,3-Trimethylbenzene; EU; Time- weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	20 ppm (1,2,3-Trimethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m³)	100 mg/m³ (Triméthylbenzène (tous isomères); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	20 ppm (Triméthylbenzène (tous isomères); Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m³)	250 mg/m³ (1,2,3-Trimethylbenzène; France; Short time value; VRC: Valeur réglementaire contraignante)
France	VLE (ppm)	50 ppm (1,2,3-Trimethylbenzène; France; Short time value; VRC: Valeur réglementaire contraignante)
France	VME (mg/m³)	100 mg/m³ (1,2,3-Trimethylbenzène; France; Time- weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	20 ppm (1,2,3-Trimethylbenzène; France; Time- weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m³)	100 mg/m³ (Mesithyleen (trimethylbenzenen); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	20 ppm (Mesithyleen (trimethylbenzenen); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	200 mg/m³ (Mesithyleen (trimethylbenzenen); Netherlands; Short time value; Public occupational exposure limit value)

20/11/2017 EN (English US) 5/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1,2,3-trimethylbenzene (526-73-8)			
Netherlands	Grenswaarde TGG 15MIN (ppm)	40 ppm (Mesithyleen (trimethylbenzenen); Netherlands; Short time value; Public occupational exposure limit value)	
United Kingdom	WEL TWA (mg/m³)	125 mg/m³ Trimethylbenzenes, all isomers or mixtures; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)	
United Kingdom	WEL TWA (ppm)	25 ppm Trimethylbenzenes, all isomers or mixtures; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)	

8.2. Exposure controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety

glasses.







Hand protection : Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical

penetration.

Eye protection : Chemical goggles or safety glasses. Safety glasses.

Skin and body protection : Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin

contact.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Colorless. Odor : characteristic. : No data available рΗ : No data available Melting point : No data available Freezing point Boiling point No data available Flash point : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Relative density : No data available
Solubility : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

20/11/2017 EN (English US) 6/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5.	Incompatible mat	امنعما	_
10.5.			SI

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

symptoms

SECTION 11: Toxicological information

Acute toxicity	: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin.			
Custom VOA Additions Mixture				
ATE CLP (oral)	103.4344370477 mg/kg body weight			
ATE CLP (dermal)	310.5602921751 mg/kg body weight			
methanol (67-56-1)				
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)			
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)			
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)			
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)			
ATE CLP (oral)	100 mg/kg body weight			
ATE CLP (dermal)	300 mg/kg body weight			
ATE CLP (gases)	700 ppmV/4h			
ATE CLP (vapors)	3 mg/l/4h			
ATE CLP (dust, mist)	0.5 mg/l/4h			
2-chloroethylvinyl ether (110-75-8)				
LD50 oral rat	250 mg/kg (Rat)			
LD50 dermal rabbit	3354 mg/kg (Rabbit)			
ATE CLP (oral)	250 mg/kg body weight			
ATE CLP (dermal)	3354 mg/kg body weight			
cyclohexane (110-82-7)				
LD50 oral rat	> 12705 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; >5000 mg/kg bodyweight; Rat)			
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)			
LC50 inhalation rat (mg/l)	> 19.07 mg/l/4h (Rat; Experimental value)			
LC50 inhalation rat (ppm)	> 5540 ppm/4h (Rat)			
methylcyclohexane (108-87-2)				
LD50 oral rat	> 5840 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Read-across)			
LD50 dermal rat	> 2800 mg/kg body weight (Rat; Read-across)			
LD50 dermal rabbit	86700 mg/kg (Rabbit; Literature study)			
Skin corrosion/irritation	: Not classified			
	Based on available data, the classification criteria are not met			
Serious eye damage/irritation	: Not classified			
	Based on available data, the classification criteria are not met			
Respiratory or skin sensitization	: Not classified			
	Based on available data, the classification criteria are not met			
Germ cell mutagenicity	: Not classified			
	Based on available data, the classification criteria are not met			
Carcinogenicity	: Not classified			
	Based on available data, the classification criteria are not met May cause cancer			
Reproductive toxicity	: Not classified			
•	Based on available data, the classification criteria are not met			
Specific target organ toxicity – single exposure	: Causes damage to organs.			
Specific target organ toxicity – repeated exposure	: Not classified Based on available data, the classification criteria are not met			
Aspiration hazard	: Not classified			
•	Based on available data, the classification criteria are not met			
Potential Adverse human health effects and	: Toxic if swallowed. Toxic in contact with skin.			

20/11/2017 EN (English US) 7/11

SECTION 12: Ecological information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.1. Toxicity	
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)
2-methyl-2-butanol (75-85-4)	
LC50 fish 1	2430 mg/l (LC50)
EC50 Daphnia 1	3185 mg/l (EC50; 24 h)
EC50 Daphnia 2	4030 mg/l (LC50)
Threshold limit algae 1	1250 mg/l (EC0; 192 h)
cyclohexane (110-82-7)	
LC50 fish 1	4.53 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	0.9 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	3.428 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
Threshold limit algae 2	0.925 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
methylcyclohexane (108-87-2)	
LC50 fish 2	5.4 mg/l (LC50; 96 h; Salmo gairdneri; Semi-static system)
Threshold limit algae 2	29 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Read-across)
12.2. Persistence and degradability	
Custom VOA Additions Mixture	
Persistence and degradability	Not established.
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O₂/g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)
2-methyl-2-butanol (75-85-4)	
Persistence and degradability	Not readily biodegradable in water.
THOD	2.70 = 0.75 = 0.05 = 0.05

Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)
2-methyl-2-butanol (75-85-4)	
Persistence and degradability	Not readily biodegradable in water.
ThOD	2.72 g O ₂ /g substance
2-chloroethylvinyl ether (110-75-8)	
Persistence and degradability	Biodegradability in soil: no data available.
cyclohexane (110-82-7)	
Persistence and degradability	Readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O₂/g substance
BOD (% of ThOD)	< 0.5 (Literature study)
methylcyclohexane (108-87-2)	
Persistence and degradability	Not readily biodegradable in water. Low potential for adsorption in soil.
1,2,3-trimethylbenzene (526-73-8)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Non degradable in the soil. Adsorbs into the soil. Photodegradation in the air.
12.3. Bioaccumulative potential	
Custom VOA Additions Mixture	
Bioaccumulative potential	Not established.
methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

20/11/2017 EN (English US) 8/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methyl-2-butanol (75-85-4)			
BCF fish 1	3 (BCF; 528 h)		
Log Pow	0.89 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
2-chloroethylvinyl ether (110-75-8)			
Log Pow	0.70 - 1.28 (Calculated)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
cyclohexane (110-82-7)			
BCF fish 2	31 - 129 (BCF; 8 weeks; Cyprinus carpio)		
Log Pow	3.44 (Experimental value; 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
methylcyclohexane (108-87-2)			
BCF fish 1	95 - 321 (BCF; 8 weeks; Cyprinus carpio)		
Log Pow	3.88 (Literature)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
1,2,3-trimethylbenzene (526-73-8)			
BCF fish 1	133 - 259 (BCF)		
Log Pow	3.66 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
12.4. Mobility in soil			
methanol (67-56-1)			
Surface tension	0.023 N/m (20 °C)		
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value		
2-methyl-2-butanol (75-85-4)			
Surface tension	0.023 N/m (20 °C)		
cyclohexane (110-82-7)			
Surface tension	0.025 N/m (20 °C)		
Log Koc	log Koc,Other; 2.89; QSAR; Koc; Other; 770; QSAR		
methylcyclohexane (108-87-2)			
Log Koc	log Koc,SRC PCKOCWIN v2.0; 2.369; Calculated value		
12.5. Results of PBT and vPvB assessment			

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

		-
14.1.	UN numbe	ж

UN-No. (ADR) : 1992 UN-No. (IATA) : 1992 UN-No. (IMDG) : 1992 UN-No. (ADN) : 1992

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Proper Shipping Name (ADN) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Transport document description (ADR) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S., 3 (6.1), II, (D/E)

14.3. Packing group

20/11/2017 EN (English US) 9/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Class (ADR)	:	3
Classification code (ADR)	:	FT1
Class (IATA)	:	3
Class (IMDG)	:	3
Class (ADN)	:	3
Classification code (ADN)	:	FT1
Subsidiary risks (ADR)	:	6.1
Subsidiary risks (IMDG)	:	6.1
Hazard labels (ADR)	:	3, 6.1



Hazard labels (IATA) : 3, 6.1



Hazard labels (IMDG) : 3, 6.1



Hazard labels (ADN) : 3, 6.1



14.4. Packing group

Packing group (ADR) : II
Packing group (IATA) : II
Packing group (IMDG) : II
Packing group (ADN) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 336 Classification code (ADR) : FT1

Orange plates :

336 1992

Special provision (ADR) : 274

Transport category (ADR) : 2

Tunnel restriction code (ADR) : D/E

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E2

14.6.2. Transport by sea

Special provision (IMDG) : 274

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP2, TP13

20/11/2017 EN (English US) 10/11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : B

Properties and observations (IMDG) : Flammable toxic liquid which is not specified by name in this class or, on account of its

characteristics, in some other class. Toxic if swallowed, by skin contact or by inhalation.

14.6.3. Air transport

CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L PCA packing instructions (IATA) : 352 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA max net quantity (IATA) : 1L PCA Excepted quantities (IATA) : E2 Special provision (IATA) : A3 ERG code (IATA) : 3HP

14.6.4. Inland waterway transport

Special provision (ADN) : 274, 802
Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E2

Carriage permitted (ADN) : T

Equipment required (ADN) : PP, EP, EX, TOX, A

Ventilation (ADN) : VE01, VE02

Number of blue cones/lights (ADN) : 2
Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance Contains no REACH Annex XIV substances.

15.1.2. National regulations

Germany

Water hazard class (WGK) : 2 - hazardous to water

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

PHV SDS EU

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

20/11/2017 EN (English US) 11/11