

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/20/2020 Revision date: 02/20/2020 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 4,4'-DDD Mix
Product code : AL0-130997

1.2. Recommended use and restrictions on use

No additional information available

1.3 Supplier

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids H225 Highly flammable liquid and vapour

Category 2

Acute toxicity (oral) H301 Toxic if swallowed

Category 3

Acute toxicity (dermal) H311 Toxic in contact with skin

Category 3

Specific target organ H370 Causes damage to organs

toxicity (single exposure)

Category 1

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapour

H301+H311 - Toxic if swallowed or in contact with skin

H370 - Causes damage to organs

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P307+P311 - If exposed: Call a poison center/doctor P312 - Call a poison center or doctor if you feel unwell

P321 - Specific treatment (see supplemental first aid instruction on this label) P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

02/20/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US

Not applicable

SECTION 3: Composition/Information on ingredients

Not applicable

Mixtures

| Name | Product identifier | Conc. |
|-------------------------|--------------------|-------|
| methanol (Component) | (CAS-No.) 67-56-1 | 99.99 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

Description of first aid measure

First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER or

doctor/physician. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. First-aid measures after skin contact

Immediately call a poison center or doctor/physician. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with First-aid measures after eye contact

water for several minutes. Obtain medical attention if pain, blinking or redness persists.

: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a First-aid measures after ingestion

poison center or doctor/physician.

Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects after skin contact Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard

Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedure

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

02/20/2020 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools.

Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before

reuse.

Conditions for safe storage, including any incompatibilities

Technical measures

Hygiene measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment.

Storage conditions

Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a

well-ventilated place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

Control parameters

| 4,4'-DDD Mix | | |
|--------------|--------------------------------|--------------------------------------|
| ACGIH | Local name | Methanol |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| ACGIH | Remark (ACGIH) | Headache; eye dam; dizziness; nausea |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m³) | 260 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |

| methanol (67-56-1) | | |
|--------------------|--------------------------------|--|
| ACGIH | Local name | Methanol |
| ACGIH | ACGIH TWA (ppm) | 200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH | ACGIH STEL (ppm) | 250 ppm (Methanol; USA; Short time value; TLV - Adopted Value) |
| ACGIH | Remark (ACGIH) | Headache; eye dam; dizziness; nausea |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m³) | 260 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |

8.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

02/20/2020 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):







Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

| 9.1. | nformation on basic physical and chemi | cal properties |
|------|--|-----------------|
| 0.1. | morrination on basic physical and chemin | iodi proportios |

Physical state : Liquid

: characteristic: No data available

: No data available

: Colorless

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour.

No data available Vapor pressure Relative vapor density at 20 °C : No data available Relative density : No data available Solubility : No data available Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available No data available Explosive properties

9.2. Other information

Oxidizing properties

No additional information available

02/20/2020 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| 4,4'-DDD Mix | |
|--------------------|--|
| ATE US (oral) | 100.01 mg/kg body weight |
| ATE US (dermal) | 300.03 mg/kg body weight |
| methanol (67-56-1) | |
| LD50 oral rat | > 5000 mg/kg (Rat: BASE test: Literature study: 1187-2769 mg/kg bodyweight: Rat: Weight of |

| > 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence) |
|--|
| 15800 mg/kg (Rabbit; Literature study) |
| 85 mg/l/4h (Rat; Literature study) |
| 64000 ppm/4h (Rat; Literature study) |
| 100 mg/kg body weight |
| 300 mg/kg body weight |
| 700 ppmV/4h |
| 3 mg/l/4h |
| 0.5 mg/l/4h |
| |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

STOT-single exposure : Causes damage to organs.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

02/20/2020 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| SECTION | 12: Eco | logical | information |
|----------|---------|---------|-------------------|
| OLUITOIT | IL. LUU | logical | IIIIOI III atioii |

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

| methanol (67-56-1) | |
|--------------------|--|
| LC50 fish 1 | 15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value) |
| EC50 Daphnia 1 | > 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value) |
| LC50 fish 2 | 10800 mg/l (LC50; 96 h; Salmo gairdneri) |

12.2. Persistence and degradability

| 4,4'-DDD Mix | |
|---------------------------------|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |
| methanol (67-56-1) | |
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O₂/g substance |
| Chemical oxygen demand (COD) | 1.42 g O₂/g substance |
| ThOD | 1.5 g O₂/g substance |
| BOD (% of ThOD) | 0.8 (Literature study) |

12.3. Bioaccumulative potential

| 4,4'-DDD Mix | |
|---------------------------|--|
| Bioaccumulative potential | Not established. |
| methanol (67-56-1) | |
| BCF fish 1 | < 10 (BCF; 72 h; Leuciscus idus) |
| Log Pow | -0.77 (Experimental value; Other) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| methanol (67-56-1) | |
|--------------------|---|
| Surface tension | 0.023 N/m (20 °C) |
| Log Koc | Koc,PCKOCWIN v1.66; 1; Calculated value |

12.5. Other adverse effects

| 4,4'-DDD Mix | | |
|--------------------|--|--|
| | | |
| methanol (67-56-1) | | |
| | | |

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1992 Flammable liquids, toxic, n.o.s. (methanol), 3 (6.1), II

UN-No.(DOT) : UN1992

02/20/2020 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.

methanol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Subsidiary risk (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132

Hazard labels (DOT) : 3 - Flammable liquid

6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is

transported by sea.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol), 3 (6.1), II, MARINE

POLLUTANT/ENVIRONMENTALLY HAZARDOÙS

UN-No. (IMDG) : 199

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Subsidiary risks (IMDG) : 6.1 - Toxic substances

Air transport

Transport document description (IATA) : UN 1992 Flammable liquid, toxic, n.o.s. (methanol), 3 (6.1), II, ENVIRONMENTALLY

HAZARDOUS

UN-No. (IATA) : 1992

02/20/2020 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger
Subsidiary hazards (IATA) : 6.1 - Toxic substances

SECTION 15: Regulatory information

15.1. US Federal regulations

methanol (67-56-1) Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

| methanol (67-56 | 6-1) | | | | |
|--|---|---|---|----------------------------------|---|
| U.S California - Proposition 65 - Carcinogens List | U.S California - Proposition 65 - Developmental Toxicity | U.S California - Proposition 65 - Reproductive Toxicity - Female | U.S California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| No | Yes | No | No | | 47000 μg/day (inhalation); 23,000 μg/day (oral) |

SECTION 16: Other information

Revision date : 02/20/2020

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases:

| Total of the prince of | | | | |
|------------------------|------|------------------------------------|--|--|
| | H225 | Highly flammable liquid and vapour | | |
| | H301 | Toxic if swallowed | | |
| | H311 | Toxic in contact with skin | | |
| | H370 | Causes damage to organs | | |

Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

02/20/2020 EN (English US) 8/8