# ertified Reference Materials

## **Endrin Standard**

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/01/2019 Revision date: 05/01/2019 Version: 1.0

## **SECTION 1: Identification**

1.1. Identification

Product form : Mixture Product name : Endrin Standard Product code AL0-101428

### Recommended use and restrictions on use

No additional information available

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

### 1.4. Emergency telephone number

**Emergency number** : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

## SECTION 2: Hazard(s) identification

### **GHS-US** classification

Flammable liquids H225 Highly flammable liquid and vapour

Category 2

Serious eye damage/eye H319 Causes serious eye irritation

irritation Category 2

Specific target organ H336 May cause drowsiness or dizziness

toxicity (single exposure)

Category 3

Full text of H statements : see section 16

## GHS Label elements, including precautionary statements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H225 - Highly flammable liquid and vapour

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

## Other hazards which do not result in classification

No additional information available

05/01/2019 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **Unknown acute toxicity (GHS US)**

Not applicable

## **SECTION 3: Composition/Information on ingredients**

### Substance

Not applicable

### Mixtur

Name	Product identifier	Conc.
acetone	(CAS-No.) 67-64-1	99.9

Full text of hazard classes and H-statements : see section 16

## **SECTION 4: First-aid measures**

## 4.1. Description of first aid measure

First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER or

doctor/physician. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. First-aid measures after skin contact Immediately call a poison center or doctor/physician. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with First-aid measures after eye contact water for several minutes. Obtain medical attention if pain, blinking or redness persists.

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a

poison center or doctor/physician.

### Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

## Immediate medical attention and special treatment, if necessary

No additional information available

First-aid measures after ingestion

## **SECTION 5: Fire-fighting measures**

## Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

## Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

**Explosion hazard** : May form flammable/explosive vapor-air mixture.

## Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedure

### 6.1.1. For non-emergency personnel

**Emergency procedures** : Evacuate unnecessary personnel.

## 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Emergency procedures** : Ventilate area.

## Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

05/01/2019 EN (English US) 2/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

## 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Additional hazards when processed

Hygiene measures

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. No open flames. No smoking. Use only non-sparking tools.

: Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water.

Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before

reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment.

Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a

well-ventilated place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight. Heat sources.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Endrin Standard		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

## 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

## Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

05/01/2019 EN (English US) 3/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## Eye protection:

Chemical goggles or safety glasses. Safety glasses

## Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

## Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

## Personal protective equipment symbol(s):









### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical propertie	9.1.	Information on	basic physica	al and chemica	properties
---	------	----------------	---------------	----------------	------------

Physical state : Liquid Color : Colorless Odor characteristic Odor threshold : No data available рΗ No data available Melting point No data available Freezing point : No data available Boiling point No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour.

Vapor pressure : No data available Relative vapor density at 20 °C No data available Relative density : No data available Solubility : No data available Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties No data available

## 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

## 10.3. Possibility of hazardous reactions

Not established.

05/01/2019 EN (English US) 4/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

## 10.5. Incompatible materials

No additional information available

## 10.6. Hazardous decomposition products

May release flammable gases.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (vapors)	76 mg/l/4h
ATE US (dust, mist)	76 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion : Toxic if swallowing a small quantity of this material will result in serious health

hazard.

## SECTION 12: Ecological information

## 12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

acetone (67-64-1)	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)

## 12.2. Persistence and degradability

Endrin Standard	
Persistence and degradability	May cause long-term adverse effects in the environment.
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O₂/g substance
Chemical oxygen demand (COD)	1.92 g O₂/g substance

05/01/2019 EN (English US) 5/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetone (67-64-1)	
ThOD	2.2 g O₂/g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

## 12.3. Bioaccumulative potential

Endrin Standard	
Bioaccumulative potential	Not established.
acetone (67-64-1)	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

## 12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

## 12.5. Other adverse effects

Other information : Avoid release to the environment.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (acetone), 3, II

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

acetone

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

05/01/2019 EN (English US) 6/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

**DOT Vessel Stowage Location** 

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number

Other information

: No supplementary information available.

## **Transportation of Dangerous Goods**

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II, MARINE POLLUTANT/ENVIRONMENTALLY

**HAZARDOUS** 

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

## Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, II, ENVIRONMENTALLY HAZARDOUS

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

## **SECTION 15: Regulatory information**

15.1. US Federal regulations

acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory  Not subject to reporting requirements of the United States SARA Section 313	
Not subject to reporting requirements of the officed States SANA Section 313	
CERCLA RQ 5000 lb	

## 15.2. International regulations

### **CANADA**

# acetone (67-64-1) Listed on the Canadian DSL (Domestic Substances List)

05/01/2019 EN (English US) 7/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **EU-Regulations**

No additional information available

## **National regulations**

No additional information available

## 15.3. US State regulations

No additional information available

## **SECTION 16: Other information**

Revision date : 05/01/2019

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

### Full text of H-phrases:

· · · · · · · · · · · · · · · · · · ·	
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

## Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any quarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

05/01/2019 EN (English US) 8/8