

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/13/2020 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : 2000 ppm Vinyl Chloride  
 Product code : AL0-131043

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Certified reference material for laboratory use only

#### 1.3. Supplier

Phenova  
 6390 Joyce Dr. Suite 100  
 Golden, CO 80403 - United States  
 T 1-866-942-2978 - F 1-866-283-0269  
[info@phenova.com](mailto:info@phenova.com) - [www.phenova.com](http://www.phenova.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924  
 ChemTel Assistance (International) +1 813-248-0585

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapour
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour  
 H302 - Harmful if swallowed  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H350 - May cause cancer  
 H370 - Causes damage to organs  
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P307+P311 - If exposed: Call a poison center/doctor  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P330 - Rinse mouth.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc.
carbon disulfide	(CAS-No.) 75-15-0	94.8
methanol (Component)	(CAS-No.) 67-56-1	5
vinyl chloride, inhibited (Component)	(CAS-No.) 75-01-4	0.2

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects after inhalation : May cause cancer by inhalation.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.  
 Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapour.  
 Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.  
 Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up in absorbent material. Collect spillage.

#### 6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
 Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.  
 Hygiene measures : Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.  
 Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.  
 Incompatible materials : Direct sunlight. Heat sources.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

2000 ppm Vinyl Chloride		
ACGIH	Local name	Carbon disulfide
ACGIH	ACGIH TWA (ppm)	1 ppm
ACGIH	Remark (ACGIH)	PNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	100 ppm 30 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2000 ppm Vinyl Chloride		
OSHA	Regulatory reference (US-OSHA)	OSHA
vinyl chloride, inhibited (75-01-4)		
ACGIH	Local name	Vinyl chloride
ACGIH	ACGIH TWA (ppm)	1 ppm (Vinyl chloride; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Lung cancer; liver dam
ACGIH	Regulatory reference	ACGIH 2018
methanol (67-56-1)		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
carbon disulfide (75-15-0)		
ACGIH	Local name	Carbon disulfide
ACGIH	ACGIH TWA (ppm)	1 ppm
ACGIH	Remark (ACGIH)	PNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	100 ppm 30 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.
OSHA	Regulatory reference (US-OSHA)	OSHA

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

#### Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: Colorless
	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

2000 ppm Vinyl Chloride	
ATE US (oral)	1254.131 mg/kg body weight

methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

carbon disulfide (75-15-0)	
LD50 oral rat	3188 mg/kg (Rat, Oral)
LC50 inhalation rat (mg/l)	25 mg/l (2 h, Rat, Inhalation)
ATE US (oral)	3188 mg/kg body weight
ATE US (vapors)	25 mg/l/4h
ATE US (dust, mist)	25 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitization : Not classified  
 Germ cell mutagenicity : Not classified  
 Based on available data, the classification criteria are not met  
 Carcinogenicity : May cause cancer.

vinyl chloride, inhibited (75-01-4)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity : Not classified  
 Based on available data, the classification criteria are not met  
 STOT-single exposure : Causes damage to organs.  
 STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.  
 Aspiration hazard : Not classified  
 Potential Adverse human health effects and symptoms : Toxic if swallowed. Toxic in contact with skin.  
 Symptoms/effects after inhalation : May cause cancer by inhalation.  
 Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.  
 Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

vinyl chloride, inhibited (75-01-4)	
EC50 Daphnia 1	119 mg/l (LC50; ECOSAR; 48 h; Daphnia sp.; Fresh water)
LC50 fish 2	210 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	77 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>methanol (67-56-1)</b>	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

<b>carbon disulfide (75-15-0)</b>	
LC50 fish 1	4 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata)
EC50 Daphnia 1	2.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna)

### 12.2. Persistence and degradability

<b>2000 ppm Vinyl Chloride</b>	
Persistence and degradability	Not established.

<b>vinyl chloride, inhibited (75-01-4)</b>	
Persistence and degradability	Not readily biodegradable in water. Biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0

<b>methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)

<b>carbon disulfide (75-15-0)</b>	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>2000 ppm Vinyl Chloride</b>	
Bioaccumulative potential	Not established.

<b>vinyl chloride, inhibited (75-01-4)</b>	
BCF fish 1	< 10 (BCF; 72 h)
BCF fish 2	3.55 l/kg (BCF; BCFWIN)
BCF other aquatic organisms 1	1100 (BCF; 120 h; Bacteria)
BCF other aquatic organisms 2	40 (BCF; 24 h)
Partition coefficient n-octanol/water (Log Pow)	1.58 (Test data; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>methanol (67-56-1)</b>	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>carbon disulfide (75-15-0)</b>	
BCF fish 1	4.3 – 8 (Pisces)
BCF fish 2	< 60 (Cyprinus carpio, Test duration: 6 weeks)
Partition coefficient n-octanol/water (Log Pow)	1.94 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>vinyl chloride, inhibited (75-01-4)</b>	
Partition coefficient n-octanol/water (Log Koc)	log Koc, SRC PCKOCWIN v1.66; 1.4; QSAR
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

<b>methanol (67-56-1)</b>	
Surface tension	0.023 N/m (20 °C)

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>methanol (67-56-1)</b>	
Partition coefficient n-octanol/water (Log Koc)	Koc,PCKOCWIN v1.66; 1; Calculated value
<b>carbon disulfide (75-15-0)</b>	
Surface tension	0.032 N/m (20 °C)

### 12.5. Other adverse effects

<b>2000 ppm Vinyl Chloride</b>	
<b>vinyl chloride, inhibited (75-01-4)</b>	
<b>methanol (67-56-1)</b>	
<b>carbon disulfide (75-15-0)</b>	

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1131 Carbon disulfide (carbon disulfide ; methanol ; vinyl chloride, inhibited), 3 (6.1), 1  
UN-No.(DOT) : UN1131  
Proper Shipping Name (DOT) : Carbon disulfide  
carbon disulfide ; methanol ; vinyl chloride, inhibited  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : I - Great Danger  
Subsidiary risk (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132  
Hazard labels (DOT) : 3 - Flammable liquid  
6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx) : 201  
DOT Packaging Bulk (49 CFR 173.xxx) : 243  
DOT Special Provisions (49 CFR 172.102) : B16 - The lading must be completely covered with nitrogen, inert gas or other inert materials.  
T14 - 6 mm Prohibited 178.275(g)(3).  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where:  $t_r$  is the maximum mean bulk temperature during transport,  $t_f$  is the temperature in degrees celsius of the liquid during filling, and  $a$  is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling ( $t_f$ ) and the maximum mean bulk temperature during transportation ( $t_r$ ) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where:  $d_{15}$  and  $d_{50}$  are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
TP7 - The vapor space must be purged of air by nitrogen or other means.  
TP13 - Self-contained breathing apparatus must be provided when this hazardous material is transported by sea.  
DOT Packaging Exceptions (49 CFR 173.xxx) : None



# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: Forbidden
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters", 78 - Stow "separated longitudinally by an intervening complete compartment or hold from" explosives, 115 - If packaged in glass or earthenware inner packaging in wooden or fiberboard outer packaging, the maximum quantity on any vessel is 500 kg (equivalent to 450 L)
Emergency Response Guide (ERG) Number	: 131
Other information	: No supplementary information available.

### Transportation of Dangerous Goods

Not applicable

### Transport by sea

Transport document description (IMDG)	: UN 1131 CARBON DISULPHIDE (carbon disulfide ; methanol ; vinyl chloride, inhibited), 3 (6.1), I (-30°C c.c.)
UN-No. (IMDG)	: 1131
Proper Shipping Name (IMDG)	: CARBON DISULPHIDE
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: I - substances presenting high danger
Subsidiary risks (IMDG)	: 6.1 - Toxic substances
Limited quantities (IMDG)	: 0

### Air transport

Transport document description (IATA)	: UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (FLAMMABLE LIQUID, TOXIC, N.O.S.), 3 (6.1), II
UN-No. (IATA)	: 1992
Proper Shipping Name (IATA)	: FLAMMABLE LIQUID, TOXIC, N.O.S.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger
Subsidiary hazards (IATA)	: 6.1 - Toxic substances

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### vinyl chloride, inhibited (75-01-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1 lb
-----------	------

#### methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>carbon disulfide (75-15-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
Listed on EPA Hazardous Air Pollutant (HAPS)	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb

### 15.2. International regulations

#### CANADA

<b>vinyl chloride, inhibited (75-01-4)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>methanol (67-56-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>carbon disulfide (75-15-0)</b>
Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

<b>vinyl chloride, inhibited (75-01-4)</b>
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on EPA Hazardous Air Pollutant (HAPS)
<b>methanol (67-56-1)</b>
Listed on EPA Hazardous Air Pollutant (HAPS)
<b>carbon disulfide (75-15-0)</b>
Listed on EPA Hazardous Air Pollutant (HAPS)

### 15.3. US State regulations

<b>vinyl chloride, inhibited (75-01-4)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	3 µg/day	
<b>methanol (67-56-1)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 µg/day (inhalation); 23,000 µg/day (oral)
<b>carbon disulfide (75-15-0)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	Yes	Yes		

# 2000 ppm Vinyl Chloride

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H350	May cause cancer
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure

Phenova US SDS REV

*Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at [www.phenova.com](http://www.phenova.com) for additional terms and conditions of sale.*