

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 02/16/2021 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : HC Cellosolves Mix
Product code : AL0-131137

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids H225 Highly flammable liquid and vapor

Category 2

Acute toxicity (oral) H301 Toxic if swallowed

Category 3

Acute toxicity (dermal) H311 Toxic in contact with skin

Category 3

Skin corrosion/irritation H315 Causes skin irritation

Category 2

Serious eye damage/eye H319 Causes serious eye irritation

irritation Category 2

Specific target organ H370 Causes damage to organs

toxicity (single exposure)

Category 1

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation H319 - Causes serious eye irritation H370 - Causes damage to organs

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

02/16/2021 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.
methanol (Component)	(CAS-No.) 67-56-1	94
butyl glycolether (Component)	(CAS-No.) 111-76-2	2
2-ethoxyethanol (Component)	(CAS-No.) 110-80-5	2
2-hexyloxyethanol (Component)	(CAS-No.) 112-25-4	2

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention.

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects

: Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

02/16/2021 EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

Hygiene measures : Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated

clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep container tightly closed and in a well-ventilated

place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HC Cellosolves Mix		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

butyl glycolether (111-76-2)		
ACGIH	Local name	2-Butoxyethanol (EGBE)
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

02/16/2021 EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-ethoxyethanol (110-80-5)		
ACGIH	Local name	2-Ethoxyethanol
ACGIH	ACGIH TWA (ppm)	5 ppm (2-Ethoxyethanol (EGEE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Male repro dam; embryo/fetal dam
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	740 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

2-hexyloxyethanol (112-25-4)

Not applicable

methanol (67-56-1)		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

8.2. Appropriate engineering controls

Appropriate engineering controls

: Either local exhaust or general room ventilation is usually required.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):







Other information:

Do not eat, drink or smoke during use.

02/16/2021 EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

: Colorless

characteristic

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Non flammable.

Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : No data available

. The data divalidate

Solubility : No data available

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosion limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

HC Cellosolves Mix		
ATE US (oral)	105.843 mg/kg body weight	
ATE US (dermal) 316.216 mg/kg body weight		
butyl glycolether (111-76-2)		
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)	

02/16/2021 EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
butyl glycolether (111-76-2)		
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))	
ATE US (oral)	1746 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	
2-ethoxyethanol (110-80-5)		
LD50 oral rat	2125 mg/kg (Rat)	
LD50 dermal rat	3900 mg/kg (Rat)	
LD50 dermal rabbit	3300 mg/kg (Rabbit)	
LC50 Inhalation - Rat	10 mg/l/4h (Rat)	
LC50 Inhalation - Rat [ppm]	2650 ppm/4h (Rat)	
ATE US (oral)	2125 mg/kg body weight	
ATE US (dermal)	3300 mg/kg body weight	
ATE US (gases)	2650 ppmV/4h	
ATE US (vapors)	10 mg/l/4h	
ATE US (dust, mist)	10 mg/l/4h	
2-hexyloxyethanol (112-25-4)		
LD50 oral rat	738 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	869.55 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Female, Experimental value, Dermal, 014 day(s))	
ATE US (oral)	738 mg/kg body weight	
ATE US (dermal)	869.55 mg/kg body weight	
methanol (67-56-1)		
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)	
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)	
LC50 Inhalation - Rat	85 mg/l/4h (Rat; Literature study)	
LC50 Inhalation - Rat [ppm]	64000 ppm/4h (Rat; Literature study)	
ATE US (oral)	100 mg/kg body weight	
ATE US (dermal)	300 mg/kg body weight	
ATE US (gases)	700 ppmV/4h	
ATE US (vapors)	3 mg/l/4h	
ATE US (dust, mist)	0.5 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
	Based on available data, the classification criteria are not met	
Carcinogenicity	: Not classified	
butyl glycolether (111-76-2)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
STOT-single exposure	Based on available data, the classification criteria are not met : Causes damage to organs.	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	

02/16/2021 EN (English US) 6/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

butyl glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
2-ethoxyethanol (110-80-5)	
LC50 fish 1	> 10000 mg/l (LC50; 96 h; Lepomis macrochirus)
EC50 Daphnia 1	> 10000 mg/l (EC50; 48 h)
2-hexyloxyethanol (112-25-4)	
LC50 fish 1	100 – 220 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	145 mg/l (DIN 38412-11, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

HC Callosolves Mix

nc cellosolves ivilx		
Persistence and degradability	Not established.	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water.	
2-ethoxyethanol (110-80-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.	
Biochemical oxygen demand (BOD)	1.03 g O₂/g substance	
Chemical oxygen demand (COD)	1.92 g O₂/g substance	
ThOD	1.9341 g O₂/g substance	
BOD (% of ThOD)	0.53	
2-hexyloxyethanol (112-25-4)		
Persistence and degradability	Readily biodegradable in water.	
Chemical oxygen demand (COD)	2.47 g O₂/g substance	

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O₂/g substance
Chemical oxygen demand (COD)	1.42 g O₂/g substance
ThOD	1.5 g O₂/g substance
BOD (% of ThOD)	0.8 (Literature study)

12.3. Bioaccumulative potential

HC Cellosolves Mix	
Bioaccumulative potential Not established.	
butyl glycolether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

02/16/2021 EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-ethoxyethanol (110-80-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.1 (Experimental value)	
Bioaccumulative potential	Bioaccumulation: not applicable.	
2-hexyloxyethanol (112-25-4)		
BCF fish 1	5.79 (Cyprinus carpio, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	1.97 (Experimental value, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
methanol (67-56-1)		
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)	
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value; Other)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

butyl glycolether (111-76-2)				
Surface tension	65.03 mN/m (20 °C, 2 g/l)			
Ecology - soil	Low potential for adsorption in soil.			
2-ethoxyethanol (110-80-5)				
Surface tension	0.028 N/m (25 °C)			
Ecology - soil	No (test)data on mobility of the substance available.			
2-hexyloxyethanol (112-25-4)				
Partition coefficient n-octanol/water (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Highly mobile in soil.			
methanol (67-56-1)				
Surface tension	0.023 N/m (20 °C)			
Partition coefficient n-octanol/water (Log Koc)	Koc,PCKOCWIN v1.66; 1; Calculated value			

12.5. Other adverse effects

HC Cellosolves Mix		
butyl glycolether (111-76-2)		
2-ethoxyethanol (110-80-5)		
2-hexyloxyethanol (112-25-4)		
methanol (67-56-1)		

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1992 Flammable liquids, toxic, n.o.s. (methanol), 3 (6.1), II

UN-No.(DOT) : UN1992

Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.

methanol

02/16/2021 EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Subsidiary risk (DOT) : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132

Hazard labels (DOT) : 3 - Flammable liquid

6.1 - Poison





DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 243

DOT Special Provisions (49 CFR 172.102)

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is

transported by sea.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location

60 L

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol), 3 (6.1), II

UN-No. (IMDG) : 1992

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Subsidiary risks (IMDG) : 6.1 - Toxic substances

Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1992 Flammable liquid, toxic, n.o.s. (methanol), 3 (6.1), II

UN-No. (IATA) : 1992

Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

Subsidiary hazards (IATA) : 6.1 - Toxic substances

02/16/2021 EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-ethoxyethanol (110-80-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag S - S - indicates a substance that is identified in a final Significant New Use Rule.

CERCLA RQ 1000 lb

2-hexyloxyethanol (112-25-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

methanol (67-56-1

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

butyl glycolether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

2-ethoxyethanol (110-80-5)

Listed on the Canadian DSL (Domestic Substances List)

2-hexyloxyethanol (112-25-4)

Listed on the Canadian DSL (Domestic Substances List)

methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

2-ethoxyethano	l (110-80-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	Yes		750 μg/day (oral); 960 μg/day (inhalation)
methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 μg/day (inhalation); 23,000 μg/day (oral)

02/16/2021 EN (English US) 10/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H370	Causes damage to organs	

Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

02/16/2021 EN (English US) 11/11