

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Custom Ag 8081 Mix
Product code : AL0-130584

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Certified reference material for laboratory use only

1.3. Details of the supplier of the safety data sheet

Phenova
6390 Joyce Dr. Suite 100
Golden, CO 80403 - United States
T 1-866-942-2978 - F 1-866-283-0269
info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924
ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
Muta. 1B H340

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour
H340 - May cause genetic defects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313 - If exposed or concerned: Get medical advice/attention.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
hexane (Component)	(CAS-No.) 110-54-3	50.61	Flam. Liq. 2, H225
toluene (Component)	(CAS-No.) 108-88-3	49	Flam. Liq. 2, H225 Muta. 1B, H340

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up in absorbent material. Collect spillage.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
- Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.
- Incompatible materials : Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Custom Ag 8081 Mix		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	Remark (ACGIH)	Visual impair; female repro;
USA OSHA	Remark (OSHA)	(2) See Table Z-2.
toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm (Toluene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	Remark (ACGIH)	Visual impair; female repro;
USA OSHA	Remark (OSHA)	(2) See Table Z-2.
hexane (110-54-3)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm (n-Hexane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	Remark (ACGIH)	CNS impair; peripheral neuropathy; eye irr; Skin; BEI
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

8.2. Exposure controls

- Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.
- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.



- Hand protection : Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration.
- Eye protection : Chemical goggles or safety glasses. Safety glasses.
- Skin and body protection : Wear suitable protective clothing. Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Other information : Do not eat, drink or smoke during use.

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless.
Odor	: characteristic.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

toluene (108-88-3)

LD50 oral rat	> 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
---------------	---

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)	
LD50 dermal rabbit	12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat; Literature study)
ATE CLP (dermal)	12223 mg/kg body weight

hexane (110-54-3)	
LD50 oral rat	16000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3350 mg/kg body weight (Rabbit; Read-across; Equivalent or similar to OECD 402)
ATE CLP (oral)	16000 mg/kg body weight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects. Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

hexane (110-54-3)	
LC50 fish 1	2.5 mg/l (LC50; 96 h)
EC50 Daphnia 1	2.1 mg/l (EC50; 48 h)
Threshold limit algae 2	26 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system)

12.2. Persistence and degradability

Custom Ag 8081 Mix	
Persistence and degradability	May cause long-term adverse effects in the environment.

toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

hexane (110-54-3)	
Persistence and degradability	Readily biodegradable in water. Photooxidation in water. Biodegradable in the soil. Low potential for mobility in soil.
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	0.63 (Literature study)

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Custom Ag 8081 Mix	
Bioaccumulative potential	Not established.
toluene (108-88-3)	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
hexane (110-54-3)	
BCF fish 1	501.187 (BCF; Other; Pimephales promelas)
Log Pow	3.5 - 3.94 (Calculated)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
hexane (110-54-3)	
Surface tension	0.018 N/m (25 °C; 1 g/l)
Log Koc	Koc,2187.76; QSAR; log Koc; 3.34; QSAR

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Transport document description : UN1993 Flammable liquids, n.o.s. (toluene), 3, II
UN-No.(DOT) : 1993
DOT NA no. : UN1993
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
toluene
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name
Packing group (DOT) : II - Medium Danger
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

ADR

Transport document description :

Transport by sea

UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	1 %

hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %

15.2. International regulations

CANADA

toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

hexane (110-54-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

hexane (110-54-3)

Custom Ag 8081 Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of H statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

toluene (108-88-3)
Listed on EPA Hazardous Air Pollutant (HAPS)
hexane (110-54-3)
Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

Custom Ag 8081 Mix()				
U.S. - California - Proposition 65 - Carcinogens List	No			
U.S. - California - Proposition 65 - Developmental Toxicity	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No			
toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
hexane (110-54-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	Yes	

SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Hazard Rating

PHV SDS US

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.