

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/05/2019 Revision date: 09/17/2019 Supersedes: 07/05/2019 Version: 2.0

## **SECTION 1: Identification**

1.1. Identification

Product form : Mixture

Product name : 8270 APPIX Spike A

Product code : AL0-130861

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

#### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids H225 Highly flammable liquid and vapour

Category 2

Skin corrosion/irritation H315 Causes skin irritation

Category 2

Full text of H statements : see section 16

# 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P321 - Specific treatment (see supplemental first aid instruction on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

## 2.3. Other hazards which do not result in classification

No additional information available

## 2.4. Unknown acute toxicity (GHS US)

Not applicable

09/17/2019 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.
tert-Butyl Methyl Ether (MTBE) (Component)	(CAS-No.) 1634-04-4	99.27

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

#### **SECTION 5: Fire-fighting measures**

# 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

No additional information available

## 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

## 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

## 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

## 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

09/17/2019 EN (English US) 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

Hygiene measures : Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated

clothing. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep container tightly closed and in a well-ventilated

place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

8270 APPIX Spike A		
ACGIH	Local name	Methyl tert-butyl ether
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam
ACGIH	Regulatory reference	ACGIH 2018

tert-Butyl Methyl Ether (MTBE) (1634-04-4)		
ACGIH	Local name	Methyl tert-butyl ether
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam
ACGIH	Regulatory reference	ACGIH 2018

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

## 8.3. Individual protection measures/Personal protective equipment

## Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

#### Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

## Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

### Respiratory protection:

Wear appropriate mask

## Personal protective equipment symbol(s):







#### Other information:

Do not eat, drink or smoke during use.

09/17/2019 EN (English US) 3/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

: Colorless

characteristic

: Non flammable.

Odor threshold : No data available

No data available

No data available Melting point Freezing point : No data available

No data available Boiling point

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : No data available

: No data available Solubility

Log Pow : No data available

: No data available Auto-ignition temperature

Decomposition temperature No data available

Viscosity, kinematic : No data available

No data available Viscosity, dynamic

**Explosion limits** No data available

: No data available Explosive properties

Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Not established.

## 10.3. Possibility of hazardous reactions

Not established.

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

# Incompatible materials

No additional information available

## 10.6. Hazardous decomposition products

No additional information available

## **SECTION 11: Toxicological information**

## Information on toxicological effects

Acute toxicity : Not classified

tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	85 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation)

09/17/2019 EN (English US) 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	<del>-</del>
tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
ATE US (vapors)	85 mg/l/4h
ATE US (dust, mist)	85 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified  Based on available data, the classification criteria are not met
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

# SECTION 12: Ecological information

#### 12.1. Toxicity

tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
LC50 fish 1	672 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	472 mg/l (US EPA, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP)

# 12.2. Persistence and degradability

8270 APPIX Spike A		
Persistence and degradability	Not established.	
tert-Butyl Methyl Ether (MTBE) (1634-04-4)		
Persistence and degradability	Not readily biodegradable in the soil. Not readily biodegradable in water.	

# 12.3. Bioaccumulative potential

8270 APPIX Spike A	
Bioaccumulative potential	Not established.
tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
BCF fish 1	1.5 (28 day(s), Cyprinus carpio, Flow-through system, Experimental value, Fresh weight)
Log Pow	1.06 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# 12.4. Mobility in soil

tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
Surface tension	19.3 mN/m (19 °C, 100 %, EU Method A.5: Surface tension)
Log Koc	1.063 - 1.354 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

# 12.5. Other adverse effects

8270 APPIX Spike A		
tert-Butyl Methyl Ether (MTBE) (1634-04-4)		

09/17/2019 EN (English US) 5/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information · Avoid release to the environment

## **SECTION 13: Disposal considerations**

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials Avoid release to the environment.

### **SECTION 14: Transport information**

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s., 3, II

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

**DOT Symbols** : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102)

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** passenger vessel carrying a number of passengers limited to not more than the larger of 25

passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

## **Transportation of Dangerous Goods**

Not applicable

#### Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II, MARINE POLLUTANT/ENVIRONMENTALLY

**HAZARDOUS** 

UN-No. (IMDG)

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

09/17/2019 EN (English US) 6/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, II, ENVIRONMENTALLY HAZARDOUS

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

#### 15.2. International regulations

#### **CANADA**

#### tert-Butyl Methyl Ether (MTBE) (1634-04-4)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

### tert-Butyl Methyl Ether (MTBE) (1634-04-4)

Listed on EPA Hazardous Air Pollutant (HAPS)

# 15.3. US State regulations

No additional information available

## **SECTION 16: Other information**

Revision date : 09/17/2019

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

# Full text of H-phrases:

H225	Highly flammable liquid and vapour
H315	Causes skin irritation

#### Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

09/17/2019 EN (English US) 7/7