

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/29/2019 Revision date: 03/29/2019 Version: 1.0

## **SECTION 1: Identification**

1.1. Identification

Product form : Mixture

Product name : EPH Surrogate Mix
Product code : AL0-130682

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Phenova

6390 Joyce Dr. Suite 100

Golden, CO 80403 - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

#### 1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924

ChemTel Assistance (International) +1 813-248-0585

# SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Flammable liquids H225 Highly flammable liquid and vapour

Category 2

Skin corrosion/irritation H315 Causes skin irritation

Category 2

Serious eye damage/eye H319 Causes serious eye irritation

irritation Category 2

Specific target organ H336 May cause drowsiness or dizziness

toxicity (single exposure)

Category 3

Specific target organ H372 Causes damage to organs through prolonged or repeated exposure

toxicity (repeated exposure)

Category 1

Full text of H statements: see section 16

# 2.2. GHS Label elements, including precautionary statements

#### **GHS-US labeling**

Hazard pictograms (GHS-US)







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

03/29/2019 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

#### Not applicable

#### 3.2. Mixtures

Name	Product identifier	Conc.
carbon disulfide (Component)	(CAS-No.) 75-15-0	50.984
acetone (Component)	(CAS-No.) 67-64-1	49

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

4.1.	Description	

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

# 5.2. Specific hazards arising from the chemical

No additional information available

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

# 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

03/29/2019 EN (English US) 2/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

Hygiene measures : Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated

clothing. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep container tightly closed and in a well-ventilated

place. Keep away from any flames or sparking source.

Incompatible materials : Direct sunlight.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

EPH Surrogate Mix

EPH Surroyate with		
ACGIH	Local name	Carbon disulfide
ACGIH	ACGIH TWA (ppm)	1 ppm
ACGIH	Remark (ACGIH)	PNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	100 ppm 30 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.
OSHA	Regulatory reference (US-OSHA)	OSHA
acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
carbon disulfide (75	-15-0)	
ACGIH	Local name	Carbon disulfide
ACGIH	ACGIH TWA (ppm)	1 ppm
ACGIH	Remark (ACGIH)	PNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	100 ppm 30 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.

03/29/2019 EN (English US) 3/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon disulfide (75-15-0)		
OSHA	Regulatory reference (US-OSHA)	OSHA

#### 3.2. Appropriate engineering controls

Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.

## 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.

#### Hand protection:

Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

#### Respiratory protection:

Wear appropriate mask

## Personal protective equipment symbol(s):









#### Other information:

**Explosion limits** 

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Color	: Colorless
Odor	: characteristic
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

03/29/2019 EN (English US) 4/9

: No data available

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

## **SECTION 11: Toxicological information**

11.1. Information on toxicological effects

Acute toxicity : Not classified

acetone (67-64-1)		
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)	
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)	
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))	
ATE US (oral)	5800 mg/kg body weight	
ATE US (dermal)	20000 mg/kg body weight	
ATE US (vapors)	76 mg/l/4h	
ATE US (dust, mist)	76 mg/l/4h	

carbon disulfide (75-15-0)	
LD50 oral rat	3188 mg/kg (Rat, Oral)
LC50 inhalation rat (mg/l)	25 mg/l (2 h, Rat, Inhalation)
ATE US (oral)	3188 mg/kg body weight
ATE US (vapors)	25 mg/l/4h
ATE US (dust, mist)	25 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity - repeated

exposure

: Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

03/29/2019 EN (English US) 5/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

# SECTION 12: Ecological information

#### 12.1. Toxicity

acetone (67-64-1)	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
carbon disulfide (75-15-0)	
LC50 fish 1	4 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata)

# 12.2. Persistence and degradability

EPH Surrogate Mix		
Persistence and degradability	Not established.	
acetone (67-64-1)		
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.43 g O₂/g substance	
Chemical oxygen demand (COD)	1.92 g O₂/g substance	
ThOD	2.2 g O₂/g substance	
BOD (% of ThOD)	0.872 (20 day(s), Literature study)	
carbon disulfide (75-15-0)		
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.	

#### 12.3. Bioaccumulative potential

EPH Surrogate Mix		
Bioaccumulative potential	Not established.	
acetone (67-64-1)		
BCF fish 1	0.69 (Pisces)	
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)	
Log Pow	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative.	
carbon disulfide (75-15-0)		
BCF fish 1	4.3 - 8 (Pisces)	
BCF fish 2	< 60 (Cyprinus carpio, Test duration: 6 weeks)	
Log Pow	1.94 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

# 12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.
carbon disulfide (75-15-0)	
Surface tension	0.032 N/m (20 °C)

# 12.5. Other adverse effects

Other information : Avoid release to the environment.

# SECTION 13: Disposal considerations

## 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

03/29/2019 EN (English US) 6/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (carbon disulfide; acetone), 3, II

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

carbon disulfide; acetone

Class (DOT) 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

**DOT Symbols** : G - Identifies PSN requiring a technical name

: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite DOT Special Provisions (49 CFR 172.102)

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal............... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** 

> passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

#### **Transportation of Dangerous Goods**

Not applicable

#### Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1L

## Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, II

03/29/2019 EN (English US) 7/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313		
CERCLA RQ	5000 lb	
carbon disulfide (75-15-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
Listed on EPA Hazardous Air Pollutant (HAPS)		
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.	
CERCLA RQ	100 lb	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb	

#### 15.2. International regulations

#### **CANADA**

#### acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

#### carbon disulfide (75-15-0)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

#### carbon disulfide (75-15-0)

Listed on EPA Hazardous Air Pollutant (HAPS)

#### 15.3. US State regulations

carbon disulfide (75-15-0)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	Yes	Yes		

## **SECTION 16: Other information**

Revision date : 03/29/2019

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

03/29/2019 EN (English US) 8/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## Full text of H-phrases:

11005	High, Samuella limid and consum	
H225	Highly flammable liquid and vapour	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H336	May cause drowsiness or dizziness	
H372	Causes damage to organs through prolonged or repeated exposure	

#### Phenova US SDS REV

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.

03/29/2019 EN (English US) 9/9