

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 02/05/2018

Revision date: :

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Diesel Fuel #2/SAE Motor Oil Mix
Product code : AL0-130312
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Laboratory Use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Certified reference material for laboratory use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Phenova
6390 Joyce Dr. Suite 100
80403 Golden, CO - United States
T 1-866-942-2978 - F 1-866-283-0269
info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924
ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Carc. 1B H350
Aquatic Chronic 3 H412

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45
R52/53

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) : Danger
Hazardous ingredients : Motor Oil
Hazard statements (CLP) : H350 - May cause cancer
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P273 - Avoid release to the environment

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308+P313 - IF exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

No labeling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methylene Chloride	(CAS No) 75-09-2 (EC-No.) 200-838-9 (EC index no) 602-004-00-3	90	Carc. 2, H351
fuel oil, diesel (Component)	(CAS No) 68334-30-5 (EC-No.) 269-822-7 (EC index no) 649-224-00-6	5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Carc. 2, H351 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Motor Oil (Component)	(CAS No) 64742-65-0 (EC-No.) 265-169-7 (EC index no) 649-474-00-6	5	Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures : Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.
Incompatible materials : Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

fuel oil, diesel (68334-30-5)		
Belgium	Limit value (mg/m ³)	100 mg/m ³ (Gazole (vapeur et aérosol) en hydrocarbures totales; Belgium; Time-weighted average exposure limit 8 h)
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m ³)	100 mg/m ³ (Diesel fuel, as total hydrocarbons; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
Motor Oil (64742-65-0)		
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Huiles minérales (brouillards); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	10 mg/m ³ (Huiles minérales (brouillards); Belgium; Short time value)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³ (Olienevel (minerale olie); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Methylene Chloride (75-09-2)		
Belgium	Limit value (mg/m ³)	177 mg/m ³ (Chlorure de méthylène; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	50 ppm (Chlorure de méthylène; Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m ³)	356 mg/m ³ (Dichlorométhane; France; Short time value; VRC: Valeur réglementaire contraignante)
France	VLE (ppm)	100 ppm (Dichlorométhane; France; Short time value; VRC: Valeur réglementaire contraignante)
France	VME (mg/m ³)	178 mg/m ³ (Dichlorométhane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	50 ppm (Dichlorométhane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methylene Chloride (75-09-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50 ppm (Dichloromethane (Methylene chloride); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
United Kingdom	WEL TWA (mg/m ³)	350 mg/m ³ Dichloromethane; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	100 ppm Dichloromethane; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	1060 mg/m ³ Dichloromethane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	300 ppm Dichloromethane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)


8.2. Exposure controls

Appropriate engineering controls

: Either local exhaust or general room ventilation is usually required.

Personal protective equipment

: Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.



Hand protection

: Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration.

Eye protection

: Chemical goggles or safety glasses. Safety glasses.

Skin and body protection

: Wear suitable protective clothing. Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information

: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless.
Odor	: characteristic.
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Relative density	: No data available
Solubility	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

fuel oil, diesel (68334-30-5)	
LD50 oral rat	> 5000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	3.6 mg/l/4h (Rat; Experimental value; 5.40 mg/l/4h; Rat; Experimental value; 4.10 mg/l/4h; Rat; Experimental value)
ATE CLP (gases)	4500 ppmV/4h
ATE CLP (vapors)	3.6 mg/l/4h
ATE CLP (dust, mist)	3.6 mg/l/4h

Methylene Chloride (75-09-2)	
LD50 oral rat	> 2000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Literature study)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer. May cause cancer
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

fuel oil, diesel (68334-30-5)	
EC50 Daphnia 1	3.4 mg/l (TLm; 48 h; Palaemonetes sp.)
LC50 fish 2	2186 mg/l (LC50; 96 h; Salmo gairdneri)

Methylene Chloride (75-09-2)	
LC50 fish 1	193 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 1	168.2 mg/l (EC50; 48 h)

12.2. Persistence and degradability

Diesel Fuel #2/SAE Motor Oil Mix	
Persistence and degradability	May cause long-term adverse effects in the environment.

fuel oil, diesel (68334-30-5)	
Persistence and degradability	Biodegradable in water. Biodegradability in soil: no data available. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.

Motor Oil (64742-65-0)	
Persistence and degradability	Biodegradability in water: no data available.

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methylene Chloride (75-09-2)	
Persistence and degradability	Not readily biodegradable in water. Biodegradable in the soil.

12.3. Bioaccumulative potential

Diesel Fuel #2/SAE Motor Oil Mix	
Bioaccumulative potential	Not established.

fuel oil, diesel (68334-30-5)	
Log Pow	> 3.5 (Literature)
Bioaccumulative potential	Bioaccumable.

Motor Oil (64742-65-0)	
Log Pow	3.9 - 6 (Calculated)
Bioaccumulative potential	No bioaccumulation data available.

Methylene Chloride (75-09-2)	
BCF fish 1	2 - 40 (BCF)
Log Pow	1.25 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Methylene Chloride (75-09-2)	
Surface tension	0.028 N/m (20 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 2810
UN-No. (IATA) : 2810
UN-No. (IMDG) : 2810
UN-No. (ADN) : 2810

14.2. UN proper shipping name

Proper Shipping Name (ADR) : TOXIC LIQUID, ORGANIC, N.O.S.
Proper Shipping Name (IATA) : Toxic liquid, organic, n.o.s.
Proper Shipping Name (IMDG) : TOXIC LIQUID, ORGANIC, N.O.S.
Proper Shipping Name (ADN) : TOXIC LIQUID, ORGANIC, N.O.S.
Transport document description (ADR) : UN 2810 TOXIC LIQUID, ORGANIC, N.O.S., 6.1, III, (E)

14.3. Packing group

Class (ADR) : 6.1
Classification code (ADR) : T1
Class (IATA) : 6.1
Class (IMDG) : 6.1
Class (ADN) : 6.1
Classification code (ADN) : T1
Hazard labels (ADR) : 6.1



Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Division (IATA) : 6.1
Hazard labels (IATA) : 6.1



Hazard labels (IMDG) : 6.1



Hazard labels (ADN) : 6.1



14.4. Packing group

Packing group (ADR) : III
Packing group (IATA) : III
Packing group (IMDG) : III
Packing group (ADN) : III


14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 60
Classification code (ADR) : T1
Orange plates :



Special provision (ADR) : 274, 614
Transport category (ADR) : 2
Tunnel restriction code (ADR) : E
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
EAC : 2X
APP : B

14.6.2. Transport by sea

Special provision (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-A
Stowage category (IMDG) : A
Properties and observations (IMDG) : Toxic if swallowed, by skin contact or by inhalation.

14.6.3. Air transport

CAO packing instructions (IATA) : 663
CAO max net quantity (IATA) : 220L
PCA packing instructions (IATA) : 655
PCA Limited quantities (IATA) : Y642
PCA limited quantity max net quantity (IATA) : 2L

Diesel Fuel #2/SAE Motor Oil Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA max net quantity (IATA)	: 60L
PCA Excepted quantities (IATA)	: E1
Special provision (IATA)	: A3, A4, A137
ERG code (IATA)	: 6L

14.6.4. Inland waterway transport

Special provision (ADN)	: 274, 614, 802
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, TOX, A
Ventilation (ADN)	: VE02
Number of blue cones/lights (ADN)	: 0
Carriage prohibited (ADN)	: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

15.1.2. National regulations

Germany

Water hazard class (WGK) : 3 - strongly hazardous to water

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

PHV SDS EU

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.