

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 16/02/2018

Revision date: :

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : tert-Butanol Standard  
Product code : AL0-101358  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Laboratory Use  
Industrial/Professional use spec : Industrial  
For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Phenova  
6390 Joyce Dr. Suite 100  
80403 Golden, CO - United States  
T 1-866-942-2978 - F 1-866-283-0269  
[info@phenova.com](mailto:info@phenova.com) - [www.phenova.com](http://www.phenova.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924  
ChemTel Assistance (International) +1 813-248-0585

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:dust,mist)	H331
STOT SE 1	H370

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11  
T; R23/24/25  
T; R39/23/24/25  
Full text of R-phrases: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS06

GHS08

Signal word (CLP) : Danger  
Hazardous ingredients : tert-Butanol; methanol  
Hazard statements (CLP) : H225 - Highly flammable liquid and vapor  
H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Precautionary statements (CLP) : H370 - Causes damage to organs
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233 - Keep container tightly closed
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray
- P270 - Do not eat, drink or smoke when using this product
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P308+P313 - IF exposed or concerned: Get medical advice/attention
- P361+P364 - Take off immediately all contaminated clothing and wash it before reuse
- P370+P378 - In case of fire: Use media other than water to extinguish
- P403+P235 - Store in a well-ventilated place. Keep cool
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

No labeling applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methanol	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X	95	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
tert-Butanol	(CAS No) 75-65-0 (EC-No.) 200-889-7 (EC index no) 603-005-00-1	5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335

Name	Product identifier	Specific concentration limits
methanol	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X	( 3 =<C < 10) STOT SE 2, H371 ( C >= 10) STOT SE 1, H370

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.
- Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
- Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.  
Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up in absorbent material. Collect spillage.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.  
Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.  
Incompatible materials : Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

methanol (67-56-1)		
EU	IOELV TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	200 ppm (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup> (Alcool méthylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	200 ppm (Alcool méthylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup> (Alcool méthylique; Belgium; Short time value)

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

methanol (67-56-1)		
Belgium	Short time value (ppm)	250 ppm (Alcool méthylique; Belgium; Short time value)
France	VLE (mg/m <sup>3</sup> )	1300 mg/m <sup>3</sup> (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	1000 ppm (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	200 ppm (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	133 mg/m <sup>3</sup> (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup> Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	200 ppm Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup> Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	250 ppm Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
tert-Butanol (75-65-0)		
Belgium	Limit value (mg/m <sup>3</sup> )	307 mg/m <sup>3</sup> (Alcool tert-butylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	100 ppm (Alcool tert-butylique; Belgium; Time-weighted average exposure limit 8 h)
France	VME (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup> (Alcool tert-butylique; France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
France	VME (ppm)	100 ppm (Alcool tert-butylique; France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm (tert-Butanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	308 mg/m <sup>3</sup> 2-Methylpropan-2-ol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	100 ppm 2-Methylpropan-2-ol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	462 mg/m <sup>3</sup> 2-Methylpropan-2-ol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	150 ppm 2-Methylpropan-2-ol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

### 8.2. Exposure controls

Appropriate engineering controls

: Either local exhaust or general room ventilation is usually required.

Personal protective equipment

: Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.



# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand protection	: Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration.
Eye protection	: Chemical goggles or safety glasses. Safety glasses.
Skin and body protection	: Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless.
Odor	: characteristic.
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Relative density	: No data available
Solubility	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Toxic if inhaled.

tert-Butanol Standard	
ATE CLP (oral)	105.263 mg/kg body weight
ATE CLP (dermal)	315.789 mg/kg body weight
ATE CLP (dust, mist)	0.517 mg/l/4h
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>methanol (67-56-1)</b>	
ATE CLP (oral)	100 mg/kg body weight
ATE CLP (dermal)	300 mg/kg body weight
ATE CLP (gases)	700 ppmV/4h
ATE CLP (vapors)	3 mg/l/4h
ATE CLP (dust, mist)	0.5 mg/l/4h

<b>tert-Butanol (75-65-0)</b>	
LD50 oral rat	3500 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (ppm)	> 10000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	3500 mg/kg body weight
ATE CLP (gases)	4500 ppmV/4h
ATE CLP (vapors)	11 mg/l/4h
ATE CLP (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met May cause cancer
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity – single exposure	: Causes damage to organs.
Specific target organ toxicity – repeated exposure	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>methanol (67-56-1)</b>	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

<b>tert-Butanol (75-65-0)</b>	
EC50 Daphnia 1	933 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	6410 mg/l (LC50; 96 h; Pimephales promelas)

### 12.2. Persistence and degradability

<b>tert-Butanol Standard</b>	
Persistence and degradability	Not established.

<b>methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

tert-Butanol (75-65-0)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.18 g O <sub>2</sub> /g substance
ThOD	2.59 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0

### 12.3. Bioaccumulative potential

tert-Butanol Standard	
Bioaccumulative potential	Not established.

methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

tert-Butanol (75-65-0)	
BCF fish 1	< 5 (BCF)
BCF fish 2	1 (BCF)
Log Pow	0.35 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value

tert-Butanol (75-65-0)	
Surface tension	0.02 N/m (25 °C)

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 1992  
UN-No. (IATA) : 1992  
UN-No. (IMDG) : 1992  
UN-No. (ADN) : 1992

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, TOXIC, N.O.S.  
Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.  
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.  
Proper Shipping Name (ADN) : FLAMMABLE LIQUID, TOXIC, N.O.S.  
Transport document description (ADR) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S., 3 (6.1), II, (D/E)

### 14.3. Packing group

Class (ADR) : 3  
Classification code (ADR) : FT1  
Class (IATA) : 3  
Class (IMDG) : 3  
Class (ADN) : 3  
Classification code (ADN) : FT1

# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Subsidiary risks (ADR) : 6.1  
Subsidiary risks (IMDG) : 6.1  
Hazard labels (ADR) : 3, 6.1



Hazard labels (IATA) : 3, 6.1



Hazard labels (IMDG) : 3, 6.1



Hazard labels (ADN) : 3, 6.1



### 14.4. Packing group

Packing group (ADR) : II  
Packing group (IATA) : II  
Packing group (IMDG) : II  
Packing group (ADN) : II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

Hazard identification number (Kemler No.) : 336  
Classification code (ADR) : FT1  
Orange plates :



Special provision (ADR) : 274  
Transport category (ADR) : 2  
Tunnel restriction code (ADR) : D/E  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E2

#### 14.6.2. Transport by sea

Special provision (IMDG) : 274  
Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T7  
Tank special provisions (IMDG) : TP2, TP13  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
Stowage category (IMDG) : B  
Properties and observations (IMDG) : Flammable toxic liquid which is not specified by name in this class or, on account of its characteristics, in some other class. Toxic if swallowed, by skin contact or by inhalation.



# tert-Butanol Standard

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.6.3. Air transport

CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
PCA packing instructions (IATA)	: 352
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA max net quantity (IATA)	: 1L
PCA Excepted quantities (IATA)	: E2
Special provision (IATA)	: A3
ERG code (IATA)	: 3HP

### 14.6.4. Inland waterway transport

Special provision (ADN)	: 274, 802
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, TOX, A
Ventilation (ADN)	: VE01, VE02
Number of blue cones/lights (ADN)	: 2
Carriage prohibited (ADN)	: No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no REACH candidate substance  
Contains no REACH Annex XIV substances.

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

PHV SDS EU

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at [www.phenova.com](http://www.phenova.com) for additional terms and conditions of sale.