

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 31/12/2017

Revision date: :

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Custom Volatiles Mix
Product code : AL0-130223
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Laboratory Use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Phenova
6390 Joyce Dr. Suite 100
80403 Golden, CO - United States
T 1-866-942-2978 - F 1-866-283-0269
info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924
ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 : H225
Acute Tox. 3 (Oral) : H301
Acute Tox. 3 (Dermal) : H311
STOT SE 1 : H370
STOT RE 2 : H373
Ozone

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
T; R23/24/25
T; R39/23/24/25
Xn; R48/20
N; R59

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS06



GHS08

Signal word (CLP) : Danger

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapor H301+H311 - Toxic if swallowed or in contact with skin H370 - Causes damage to organs H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P260 - Do not breathe dust/fume/gas/mist/vapors/spray P270 - Do not eat, drink or smoke when using this product P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water P308+P313 - IF exposed or concerned: Get medical advice/attention P361+P364 - Take off immediately all contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use media other than water to extinguish P403+P235 - Store in a well-ventilated place. Keep cool P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
EUH phrases	: EUH059 - Hazardous to the ozone layer
No labeling applicable	

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methanol (Component)	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X	99	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
carbon disulfide (Component)	(CAS No) 75-15-0 (EC-No.) 200-843-6 (EC index no) 006-003-00-3	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361fd STOT RE 1, H372
cyclohexane (Component)	(CAS No) 110-82-7 (EC-No.) 203-806-2 (EC index no) 601-017-00-1	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
methylcyclohexane (Component)	(CAS No) 108-87-2 (EC-No.) 203-624-3 (EC index no) 601-018-00-7	0.2	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
1,1,2-trichloro-1,2,2-trifluoroethane (Component)	(CAS No) 76-13-1 (EC-No.) 200-936-1	0.2	Aquatic Chronic 2, H411 Ozone

Name	Product identifier	Specific concentration limits
methanol (Component)	(CAS No) 67-56-1 (EC-No.) 200-659-6 (EC index no) 603-001-00-X	(3 =<C < 10) STOT SE 2, H371 (C >= 10) STOT SE 1, H370
carbon disulfide (Component)	(CAS No) 75-15-0 (EC-No.) 200-843-6 (EC index no) 006-003-00-3	(0.2 =<C < 1) STOT RE 2, H373 (C >= 1) STOT RE 1, H372 (C >= 1) Repr. 2, H361fd

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
- Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools.
- Hygiene measures : Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
- Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.
- Incompatible materials : Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

carbon disulfide (75-15-0)		
EU	IOELV TWA (mg/m ³)	15 mg/m ³ (Carbon disulphide; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	5 ppm (Carbon disulphide; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	3.16 mg/m ³ (Carbone (sulfure de); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	1 ppm (Carbone (sulfure de); Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m ³)	75 mg/m ³ (Sulfure de carbone; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	25 ppm (Sulfure de carbone; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m ³)	15 mg/m ³ (Sulfure de carbone; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	5 ppm (Sulfure de carbone; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1 ppm (Carbon disulfide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	15 mg/m ³ (Zwavelkoolstof; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	4.74 ppm (Zwavelkoolstof; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	15 mg/m ³ Carbon disulphide; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	5 ppm Carbon disulphide; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
cyclohexane (110-82-7)		
EU	IOELV TWA (mg/m ³)	700 mg/m ³ (Cyclohexane; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	200 ppm (Cyclohexane; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	350 mg/m ³ (Cyclohexane; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	100 ppm (Cyclohexane; Belgium; Time-weighted average exposure limit 8 h)
France	VLE (mg/m ³)	1300 mg/m ³ (Cyclohexane; France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	375 ppm (Cyclohexane; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m ³)	700 mg/m ³ (Cyclohexane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	200 ppm (Cyclohexane; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm (Cyclohexane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	700 mg/m ³ (Cyclohexaan; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	200 ppm (Cyclohexaan; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	1400 mg/m ³ (Cyclohexaan; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	400 ppm (Cyclohexaan; Netherlands; Short time value; Public occupational exposure limit value)

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexane (110-82-7)		
United Kingdom	WEL TWA (mg/m ³)	350 mg/m ³ Cyclohexane; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	100 ppm Cyclohexane; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	1050 mg/m ³ Cyclohexane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	300 ppm Cyclohexane; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
methylcyclohexane (108-87-2)		
Belgium	Limit value (mg/m ³)	1633 mg/m ³ (Méthylcyclohexane; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	400 ppm (Méthylcyclohexane; Belgium; Time-weighted average exposure limit 8 h)
France	VME (mg/m ³)	1600 mg/m ³ (Méthylcyclohexane; France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
France	VME (ppm)	400 ppm (Méthylcyclohexane; France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	400 ppm (Methyl cyclohexane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)		
Belgium	Limit value (mg/m ³)	7781 mg/m ³ (1,1,2-Trichloro-1,2,2-trifluoroéthane; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	1000 ppm (1,1,2-Trichloro-1,2,2-trifluoroéthane; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	9729 mg/m ³ (1,1,2-Trichloro-1,2,2-trifluoroéthane; Belgium; Short time value)
Belgium	Short time value (ppm)	1250 ppm (1,1,2-Trichloro-1,2,2-trifluoroéthane; Belgium; Short time value)
France	VLE (mg/m ³)	9500 mg/m ³ (1,1,2-Trichlorotrifluoroéthane (F 113); France; Short time value; VL: Valeur non réglementaire indicative)
France	VLE (ppm)	1250 ppm (1,1,2-Trichlorotrifluoroéthane (F 113); France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m ³)	7600 mg/m ³ (1,1,2-Trichlorotrifluoroéthane (F 113); France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
France	VME (ppm)	1000 ppm (1,1,2-Trichlorotrifluoroéthane (F 113); France; Time-weighted average exposure limit 8 h; VL: Valeur non réglementaire indicative)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1000 ppm (1,1,2-Trichloro-1,2,2-trifluoroethane; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	1250 ppm (1,1,2-Trichloro-1,2,2-trifluoroethane; USA; Short time value; TLV - Adopted Value)
methanol (67-56-1)		
EU	IOELV TWA (mg/m ³)	260 mg/m ³ (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	200 ppm (Methanol; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	266 mg/m ³ (Alcool méthylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	200 ppm (Alcool méthylique; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	333 mg/m ³ (Alcool méthylique; Belgium; Short time value)
Belgium	Short time value (ppm)	250 ppm (Alcool méthylique; Belgium; Short time value)
France	VLE (mg/m ³)	1300 mg/m ³ (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

methanol (67-56-1)		
France	VLE (ppm)	1000 ppm (Methanol; France; Short time value; VL: Valeur non réglementaire indicative)
France	VME (mg/m ³)	260 mg/m ³ (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
France	VME (ppm)	200 ppm (Methanol; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	133 mg/m ³ (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm (Methanol; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	266 mg/m ³ Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	200 ppm Methanol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	333 mg/m ³ Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	250 ppm Methanol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

8.2. Exposure controls

- Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.
- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.



- Hand protection : Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration.
- Eye protection : Chemical goggles or safety glasses. Safety glasses.
- Skin and body protection : Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Colorless.
- Odor : characteristic.
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Highly flammable liquid and vapor
- Relative density : No data available
- Solubility : No data available
- Explosive properties : No data available

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidizing properties : No data available

Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin.

Custom Volatiles Mix	
ATE CLP (oral)	101.0101010101 mg/kg body weight
ATE CLP (dermal)	303.0303030303 mg/kg body weight
carbon disulfide (75-15-0)	
LD50 oral rat	3188 mg/kg (Rat)
ATE CLP (oral)	3188 mg/kg body weight
cyclohexane (110-82-7)	
LD50 oral rat	> 12705 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; >5000 mg/kg bodyweight; Rat)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 19.07 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	> 5540 ppm/4h (Rat)
methylocyclohexane (108-87-2)	
LD50 oral rat	> 5840 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Read-across)
LD50 dermal rat	> 2800 mg/kg body weight (Rat; Read-across)
LD50 dermal rabbit	86700 mg/kg (Rabbit; Literature study)
1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)	
LD50 oral rat	43000 mg/kg (Rat)
LD50 dermal rabbit	> 11000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	300 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	38500 ppm/4h (Rat)
ATE CLP (oral)	43000 mg/kg body weight
ATE CLP (gases)	38500 ppmV/4h
ATE CLP (vapors)	300 mg/l/4h
ATE CLP (dust, mist)	300 mg/l/4h
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	100 mg/kg body weight
ATE CLP (dermal)	300 mg/kg body weight
ATE CLP (gases)	700 ppmV/4h
ATE CLP (vapors)	3 mg/l/4h
ATE CLP (dust, mist)	0.5 mg/l/4h

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin corrosion/irritation	: Not classified Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met May cause cancer
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity – single exposure	: Causes damage to organs.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - air : Dangerous for the ozone layer.

carbon disulfide (75-15-0)	
LC50 fish 2	4 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Poecilia reticulata)
EC50 Daphnia 2	2.1 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
Threshold limit algae 1	21 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 96 h; Chlorella sp.)
cyclohexane (110-82-7)	
LC50 fish 1	4.53 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	0.9 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	3.428 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
Threshold limit algae 2	0.925 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
methylcyclohexane (108-87-2)	
LC50 fish 2	5.4 mg/l (LC50; 96 h; Salmo gairdneri; Semi-static system)
Threshold limit algae 2	29 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Read-across)
1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)	
EC50 Daphnia 1	71 mg/l (EC50; 48 h)
LC50 fish 2	7.4 mg/l (LC50; 96 h; Salmo gairdneri)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

Custom Volatiles Mix	
Persistence and degradability	Not established.
carbon disulfide (75-15-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradability in soil: no data available.
cyclohexane (110-82-7)	
Persistence and degradability	Readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in soil.

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexane (110-82-7)	
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O ₂ /g substance
BOD (% of ThOD)	< 0.5 (Literature study)

methylcyclohexane (108-87-2)	
Persistence and degradability	Not readily biodegradable in water. Low potential for adsorption in soil.

1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)	
Persistence and degradability	Not readily biodegradable in water. Biodegradable in the soil under anaerobic conditions.

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)

12.3. Bioaccumulative potential

Custom Volatiles Mix	
Bioaccumulative potential	Not established.

carbon disulfide (75-15-0)	
BCF fish 1	4.3 - 8 (BCF)
BCF fish 2	< 60 (BCF)
Log Pow	1.94 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

cyclohexane (110-82-7)	
BCF fish 2	31 - 129 (BCF; 8 weeks; Cyprinus carpio)
Log Pow	3.44 (Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

methylcyclohexane (108-87-2)	
BCF fish 1	95 - 321 (BCF; 8 weeks; Cyprinus carpio)
Log Pow	3.88 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)	
BCF fish 1	11 - 86 (BCF)
Log Pow	1.66 - 3.3 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

carbon disulfide (75-15-0)	
Surface tension	0.032 N/m (20 °C)

cyclohexane (110-82-7)	
Surface tension	0.025 N/m (20 °C)
Log Koc	log Koc,Other; 2.89; QSAR; Koc; Other; 770; QSAR

methylcyclohexane (108-87-2)	
Log Koc	log Koc, SRC PCKOCWIN v2.0; 2.369; Calculated value

1,1,2-trichloro-1,2,2-trifluoroethane (76-13-1)	
Surface tension	0.023 N/m

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1992
UN-No. (IATA) : 1992
UN-No. (IMDG) : 1992
UN-No. (ADN) : 1992

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, TOXIC, N.O.S.
Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S.
Proper Shipping Name (ADN) : FLAMMABLE LIQUID, TOXIC, N.O.S.
Transport document description (ADR) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S., 3 (6.1), II, (D/E)

14.3. Packing group

Class (ADR) : 3
Classification code (ADR) : FT1
Class (IATA) : 3
Class (IMDG) : 3
Class (ADN) : 3
Classification code (ADN) : FT1
Subsidiary risks (ADR) : 6.1
Subsidiary risks (IMDG) : 6.1
Hazard labels (ADR) : 3, 6.1



Hazard labels (IATA) : 3, 6.1



Hazard labels (IMDG) : 3, 6.1



Hazard labels (ADN) : 3, 6.1



14.4. Packing group

Packing group (ADR) : II
Packing group (IATA) : II
Packing group (IMDG) : II
Packing group (ADN) : II

14.5. Environmental hazards

Other information : No supplementary information available.

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 336
Classification code (ADR) : FT1
Orange plates :



Special provision (ADR) : 274
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 11
Excepted quantities (ADR) : E2

14.6.2. Transport by sea

Special provision (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP2, TP13
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : B
Properties and observations (IMDG) : Flammable toxic liquid which is not specified by name in this class or, on account of its characteristics, in some other class. Toxic if swallowed, by skin contact or by inhalation.

14.6.3. Air transport

CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
PCA packing instructions (IATA) : 352
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA max net quantity (IATA) : 1L
PCA Excepted quantities (IATA) : E2
Special provision (IATA) : A3
ERG code (IATA) : 3HP

14.6.4. Inland waterway transport

Special provision (ADN) : 274, 802
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EP, EX, TOX, A
Ventilation (ADN) : VE01, VE02
Number of blue cones/lights (ADN) : 2
Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no REACH candidate substance
Contains no REACH Annex XIV substances.

Custom Volatiles Mix

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

Germany

Water hazard class (WGK) : 1 - slightly hazardous to water

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

PHV SDS EU

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.